

Revision date: 21/12/2016

Revision: 0

CP1511 v1.2 RS 764-3039

## SAFETY DATA SHEET

### RS Matt Black Spray Paint

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

**Product name** RS Matt Black Spray Paint  
**Product number** 764-3039, ZP

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Paint.  
**Uses advised against** No specific uses advised against are identified.

##### 1.3. Details of the supplier of the safety data sheet

**Supplier**  
 RS COMPONENTS  
 BIRCHINGTON ROAD  
 CORBY  
 NORTHANTS NN17 9RS UK  
 +44 (0) 1536 402888 (8am to 8pm)  
 +44 (0) 1536 401588  
 RCustomerServicesUK@rs-components.com

##### 1.4. Emergency telephone number

**Emergency telephone** +44 (0)1865 407333

#### SECTION 2: Hazards identification


##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)

**Physical hazards** Aerosol 1 - H222, H229  
**Health hazards** Eye Irrit. 2 - H319 STOT SE 3 - H336  
**Environmental hazards** Not Classified

##### 2.2. Label elements

###### Pictogram



**Signal word** Danger

**Hazard statements**  
 H222 Extremely flammable aerosol.  
 H229 Pressurised container: may burst if heated  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.



## RS Matt Black Spray Paint

<b>xylene</b>		<b>5-10%</b>
CAS number: 1330-20-7	EC number: 215-535-7	REACH registration number: 01-2119488216-32-XXXX
<b>Classification</b>		
Flam. Liq. 3 - H226		
Acute Tox. 4 - H312		
Acute Tox. 4 - H332		
Skin Irrit. 2 - H315		
<b>1-Methoxy-2-propanol</b>		<b>1-5%</b>
CAS number: 107-98-2	EC number: 203-539-1	REACH registration number: 01-2119457435-35-XXXX
<b>Classification</b>		
Flam. Liq. 3 - H226		
STOT SE 3 - H336		
<b>butanone</b>		<b>1-5%</b>
CAS number: 78-93-3	EC number: 201-159-0	REACH registration number: 01-2119457290-43-XXXX
<b>Classification</b>		
Flam. Liq. 2 - H225		
Eye Irrit. 2 - H319		
STOT SE 3 - H336		

The full text for all hazard statements is displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	Get medical attention immediately. Show this Safety Data Sheet to the medical personnel.
<b>Inhalation</b>	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Remove any dentures. Give a few small glasses of water or milk to drink. Stop if the affected person feels sick as vomiting may be dangerous. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Place unconscious person on their side in the recovery position and ensure breathing can take place. Maintain an open airway. Loosen tight clothing such as collar, tie or belt.
<b>Skin contact</b>	Rinse with water.
<b>Eye contact</b>	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 10 minutes.
<b>Protection of first aiders</b>	First aid personnel should wear appropriate protective equipment during any rescue.

## RS Matt Black Spray Paint

### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	No specific symptoms known.
<b>Ingestion</b>	No specific symptoms known.
<b>Skin contact</b>	No specific symptoms known.
<b>Eye contact</b>	No specific symptoms known. May be slightly irritating to eyes.

### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	Treat symptomatically.
-----------------------------	------------------------

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	The product is not flammable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

<b>Specific hazards</b>	None known.
<b>Hazardous combustion products</b>	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

### 5.3. Advice for firefighters

<b>Protective actions during firefighting</b>	Avoid breathing fire gases or vapours. Evacuate area. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak.
<b>Special protective equipment for firefighters</b>	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material.
-----------------------------	---

### 6.2. Environmental precautions

<b>Environmental precautions</b>	Large Spillages: Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).
----------------------------------	--

### 6.3. Methods and material for containment and cleaning up

## RS Matt Black Spray Paint

**Methods for cleaning up**      Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Approach the spillage from upwind. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

### 6.4. Reference to other sections

**Reference to other sections**      For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

**SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

**Usage precautions**      Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from food, drink and animal feeding stuffs. Do not handle until all safety precautions have been read and understood. Do not handle broken packages without protective equipment.

**Advice on general occupational hygiene**      Wash promptly if skin becomes contaminated. Take off contaminated clothing. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Change work clothing daily before leaving workplace.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions**      Store away from incompatible materials (see Section 10). Store in accordance with local regulations. Keep only in the original container. Keep container tightly closed, in a cool, well ventilated place. Keep containers upright. Protect containers from damage. Bund storage facilities to prevent soil and water pollution in the event of spillage. The storage area floor should be leak-tight, jointless and not absorbent.

**Storage class**      Unspecified storage.

### 7.3. Specific end use(s)

**Specific end use(s)**      The identified uses for this product are detailed in Section 1.2.

**SECTION 8: Exposure Controls/personal protection**

### 8.1. Control parameters

#### Occupational exposure limits

**Acetone**

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m<sup>3</sup>  
 Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m<sup>3</sup>

**Petroleum gases, liquefied**

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m<sup>3</sup>  
 Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m<sup>3</sup>

**2-Methoxy-1-methylethyl acetate**

Long-term exposure limit (8-hour TWA): WEL 50 ppm 274 mg/m<sup>3</sup>  
 Short-term exposure limit (15-minute): WEL 100 ppm 548 mg/m<sup>3</sup>  
 Sk

**xylene**

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m<sup>3</sup>  
 Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m<sup>3</sup>  
 Sk



## RS Matt Black Spray Paint

### 1-Methoxy-2-propanol

Long-term exposure limit (8-hour TWA): WEL 100 ppm 375 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 150 ppm 560 mg/m<sup>3</sup>

Sk

### butanone

Long-term exposure limit (8-hour TWA): WEL 200 ppm 600 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 300 ppm 899 mg/m<sup>3</sup>

Sk

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

## 8.2. Exposure controls

### Protective equipment



### Appropriate engineering controls

Provide adequate ventilation. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Use process enclosures, local exhaust ventilation or other engineering controls as the primary means to minimise worker exposure. Personal protective equipment should only be used if worker exposure cannot be controlled adequately by the engineering control measures. Ensure control measures are regularly inspected and maintained. Ensure operatives are trained to minimise exposure.

### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Personal protective equipment for eye and face protection should comply with European Standard EN166. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

### Other skin and body protection

Appropriate footwear and additional protective clothing complying with an approved standard should be worn if a risk assessment indicates skin contamination is possible.

### Hygiene measures

Provide eyewash station and safety shower. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Clean equipment and the work area every day. Good personal hygiene procedures should be implemented. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Preventive industrial medical examinations should be carried out. Warn cleaning personnel of any hazardous properties of the product.

### Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with European Standard EN14387. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

## RS Matt Black Spray Paint

**Environmental exposure controls** Keep container tightly sealed when not in use.

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Aerosol.
<b>Colour</b>	Black.
<b>Odour</b>	Solvent.
<b>pH</b>	Not available.
<b>Melting point</b>	Not available.
<b>Initial boiling point and range</b>	-41°C/-41.8°F
<b>Flash point</b>	-40°C/-40°F CC (Closed cup).
<b>Evaporation rate</b>	Not available.
<b>Evaporation factor</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	Lower flammable/explosive limit: 0.8 % Upper flammable/explosive limit: 13.1%
<b>Vapour pressure</b>	Not available.
<b>Vapour density</b>	Not available.
<b>Bulk density</b>	0.728 kg/l
<b>Solubility(ies)</b>	Insoluble in water.
<b>Partition coefficient</b>	Not available.
<b>Auto-ignition temperature</b>	270°C/518°F
<b>Decomposition Temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Explosive properties</b>	Not considered to be explosive.
<b>Oxidising properties</b>	Does not meet the criteria for classification as oxidising.

#### 9.2. Other information

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

**Reactivity** See the other subsections of this section for further details.

#### 10.2. Chemical stability

**Stability** Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.

#### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** No potentially hazardous reactions known.

#### 10.4. Conditions to avoid

## RS Matt Black Spray Paint

**Conditions to avoid** There are no known conditions that are likely to result in a hazardous situation.

### 10.5. Incompatible materials

**Materials to avoid** No specific material or group of materials is likely to react with the product to produce a hazardous situation.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapours.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity - oral

**Notes (oral LD<sub>50</sub>)** Based on available data the classification criteria are not met.

#### Acute toxicity - dermal

**Notes (dermal LD<sub>50</sub>)** Based on available data the classification criteria are not met.

**ATE dermal (mg/kg)** 14,666.67

#### Acute toxicity - inhalation

**Notes (inhalation LC<sub>50</sub>)** Based on available data the classification criteria are not met.

**ATE inhalation (gases ppm)** 60,000.0

**ATE inhalation (vapours mg/l)** 146.67

**ATE inhalation (dusts/mists mg/l)** 20.0

#### Skin corrosion/irritation

**Animal data** Based on available data the classification criteria are not met.

#### Serious eye damage/irritation

**Serious eye damage/irritation** Based on available data the classification criteria are not met.

#### Respiratory sensitisation

**Respiratory sensitisation** Based on available data the classification criteria are not met.

#### Skin sensitisation

**Skin sensitisation** Based on available data the classification criteria are not met.

#### Germ cell mutagenicity

**Genotoxicity - in vitro** Based on available data the classification criteria are not met.

#### Carcinogenicity

**Carcinogenicity** Based on available data the classification criteria are not met.

#### **IARC carcinogenicity**

None of the ingredients are listed or exempt.

#### Reproductive toxicity

**Reproductive toxicity - fertility** Based on available data the classification criteria are not met.

#### **Reproductive toxicity - development**

Based on available data the classification criteria are not met.

#### Specific target organ toxicity - single exposure

**STOT - single exposure** Not classified as a specific target organ toxicant after a single exposure.



## RS Matt Black Spray Paint

**Specific target organ toxicity - repeated exposure**

**STOT - repeated exposure** Not classified as a specific target organ toxicant after repeated exposure.

**Aspiration hazard**

**Aspiration hazard** Based on available data the classification criteria are not met.

**General information**

The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

**Inhalation**

No specific symptoms known.

**Ingestion**

No specific symptoms known.

**Skin contact**

No specific symptoms known.

**Eye contact**

No specific symptoms known.

**Target organs**

No specific target organs known.

### Acetone

**Acute toxicity - oral**

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 5,800.0

**Species** Rat

**ATE oral (mg/kg)** 5,800.0

**Acute toxicity - inhalation**

**Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l)** 76.0

**Species** Rat

**ATE inhalation (vapours mg/l)** 76.0

### Petroleum gases, liquefied

**Toxicological effects** Not regarded as a health hazard under current legislation.

**Germ cell mutagenicity**

**Genotoxicity - in vitro** Chromosome aberration: Negative. REACH dossier information. Based on available data the classification criteria are not met.

**Genotoxicity - in vivo** Chromosome aberration: Negative. REACH dossier information. Based on available data the classification criteria are not met.

**Carcinogenicity**

**Carcinogenicity** NOAEL 10000 ppm, Inhalation, Mouse REACH dossier information. Based on available data the classification criteria are not met.

**Reproductive toxicity**

**Reproductive toxicity - fertility** Fertility - NOAEC 9000 ppm, Inhalation, Rat F1 REACH dossier information. Based on available data the classification criteria are not met.

**Reproductive toxicity - development** Developmental toxicity: - NOAEC: 10426 ppm, Inhalation, Rat REACH dossier information. Based on available data the classification criteria are not met.

## RS Matt Black Spray Paint

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** NOAEC 10000 ppmV/4hr/day, Inhalation, Rat REACH dossier information. Based on available data the classification criteria are not met.

### xylene

#### Acute toxicity - dermal

**ATE dermal (mg/kg)** 1,100.0

#### Acute toxicity - inhalation

**Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l)** 27.571

**Species** Mouse

**ATE inhalation (vapours mg/l)** 27.571

#### Carcinogenicity

**IARC carcinogenicity** IARC Group 3 Not classifiable as to its carcinogenicity to humans.

### 1-Methoxy-2-propanol

#### Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 3,739.0

**Species** Rat

**Notes (oral LD<sub>50</sub>)** LD<sub>50</sub> 3739 mg/kg, Oral, Rat REACH dossier information. Based on available data the classification criteria are not met.

**ATE oral (mg/kg)** 3,739.0

#### Acute toxicity - dermal

**Notes (dermal LD<sub>50</sub>)** LD<sub>50</sub> >2000 mg/kg, Dermal, Rat REACH dossier information. Based on available data the classification criteria are not met.

#### Skin corrosion/irritation

**Animal data** Dose: 0.5 mL, 4 hours, Rabbit Erythema/eschar score: No erythema (0). Oedema score: No oedema (0). REACH dossier information. Based on available data the classification criteria are not met.

#### Skin sensitisation

**Skin sensitisation** Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising. REACH dossier information. Based on available data the classification criteria are not met.

#### Germ cell mutagenicity

**Genotoxicity - in vitro** Gene mutation: Negative. REACH dossier information. Based on available data the classification criteria are not met.

**Genotoxicity - in vivo** Chromosome aberration: Negative. REACH dossier information. Based on available data the classification criteria are not met.

#### Carcinogenicity

**Carcinogenicity** NOEL 3000 ppm, Inhalation, Mouse REACH dossier information. Based on available data the classification criteria are not met.

## RS Matt Black Spray Paint

### Reproductive toxicity

**Reproductive toxicity - fertility** Two-generation study - NOAEL 1000 ppm, Inhalation, Rat F1 REACH dossier information. Based on available data the classification criteria are not met.

**Reproductive toxicity - development** Teratogenicity: - NOAEL: 1500 ppm, Inhalation, Rat REACH dossier information. Based on available data the classification criteria are not met.

### Specific target organ toxicity - single exposure

**STOT - single exposure** STOT SE 3 - H336 May cause drowsiness or dizziness. REACH dossier information.

**Target organs** Central nervous system Brain

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** NOAEL 919 mg/kg/day, Oral, Rat REACH dossier information. Based on available data the classification criteria are not met.

## SECTION 12: Ecological Information

**Ecotoxicity** Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

### 12.1. Toxicity

**Toxicity** Based on available data the classification criteria are not met.

#### Petroleum gases, liquefied

**Toxicity** Aquatic toxicity is unlikely to occur. Based on available data the classification criteria are not met.

**Acute toxicity - fish** LC<sub>50</sub>, 96 hours: 147.54 mg/l, Freshwater fish  
Estimated value.

**Acute toxicity - aquatic invertebrates** EC<sub>50</sub>, 48 hours: 16.33 mg/l, Daphnia magna  
Estimated value.

**Acute toxicity - aquatic plants** EC<sub>50</sub>, 96 hours: 11.89 mg/l, Freshwater algae  
Estimated value.

#### 1-Methoxy-2-propanol

**Acute toxicity - fish** LC<sub>50</sub>, 96 hours: 20800 mg/l, Pimephales promelas (Fat-head Minnow)  
REACH dossier information.

**Acute toxicity - aquatic invertebrates** LC<sub>50</sub>, 48 hours: 21100 mg/l, Daphnia magna  
REACH dossier information.

**Acute toxicity - aquatic plants** EC<sub>50</sub>, 7 days: >1000 mg/l, Selenastrum capricornutum  
REACH dossier information.

### 12.2. Persistence and degradability

**Persistence and degradability** The degradability of the product is not known.

#### Petroleum gases, liquefied

**Persistence and degradability** The substance is readily biodegradable.

## RS Matt Black Spray Paint

**Biodegradation** Water - Degradation 100%: 385.5 hours

### 1-Methoxy-2-propanol

**Persistence and degradability** The substance is readily biodegradable.

**Phototransformation** Water - DT<sub>50</sub>: 3.1 hours  
REACH dossier information.

**Biodegradation** Water - Degradation 96%: 28 days  
REACH dossier information.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

**Partition coefficient** Not available.

### Petroleum gases, liquefied

**Bioaccumulative potential** No data available on bioaccumulation.

### 1-Methoxy-2-propanol

**Bioaccumulative potential** No data available on bioaccumulation.

**Partition coefficient** log Pow: <1 REACH dossier information.

### 12.4. Mobility in soil

**Mobility** No data available.

### Petroleum gases, liquefied

**Mobility** The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

### 1-Methoxy-2-propanol

**Mobility** Mobile.

**Surface tension** 70.7 mN/m @ 20°C

### 12.5. Results of PBT and vPvB assessment

### Petroleum gases, liquefied

**Results of PBT and vPvB assessment** This substance is not classified as PBT or vPvB according to current EU criteria.

### 1-Methoxy-2-propanol

**Results of PBT and vPvB assessment** This substance is not classified as PBT or vPvB according to current EU criteria.

### 12.6. Other adverse effects

**Other adverse effects** None known.

## RS Matt Black Spray Paint

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

**General information**      The generation of waste should be minimised or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

**Disposal methods**      Do not empty into drains. Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labelled with their contents. Waste packaging should be collected for reuse or recycling. Incineration or landfill should only be considered when recycling is not feasible.

### SECTION 14: Transport information

#### 14.1. UN number

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (ADN)	1950

#### 14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS

#### 14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

#### Transport labels



#### 14.4. Packing group

ADR/RID packing group	None
-----------------------	------

## RS Matt Black Spray Paint

IMDG packing group            None

ADN packing group            None

ICAO packing group          None

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

### 14.6. Special precautions for user

EmS                                F-D, S-U

ADR transport category        2

Tunnel restriction code        (D)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to    Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**National regulations**            Health and Safety at Work etc. Act 1974 (as amended).  
The Carriage of Dangerous Goods and Use of Transportable Pressure Equipment Regulations 2009 (SI 2009 No. 1348) (as amended) ["CDG 2009"].  
EH40/2005 Workplace exposure limits.

**EU legislation**                    Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).  
Commission Regulation (EU) No 2015/830 of 28 May 2015.  
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### Inventories

#### **EU - EINECS/ELINCS**

None of the ingredients are listed or exempt.

## SECTION 16: Other information



## RS Matt Black Spray Paint

<b>Abbreviations and acronyms used in the safety data sheet</b>	<p>ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.</p> <p>ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.</p> <p>RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.</p> <p>IATA: International Air Transport Association.</p> <p>ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air.</p> <p>IMDG: International Maritime Dangerous Goods.</p> <p>CAS: Chemical Abstracts Service.</p> <p>ATE: Acute Toxicity Estimate.</p> <p>LC<sub>50</sub>: Lethal Concentration to 50 % of a test population.</p> <p>LD<sub>50</sub>: Lethal Dose to 50% of a test population (Median Lethal Dose).</p> <p>EC<sub>50</sub>: 50% of maximal Effective Concentration.</p> <p>PBT: Persistent, Bioaccumulative and Toxic substance.</p> <p>vPvB: Very Persistent and Very Bioaccumulative.</p>
<b>Training advice</b>	Read and follow manufacturer's recommendations. Only trained personnel should use this material.
<b>Issued by</b>	Bethan Massey
<b>Revision date</b>	21/12/2016
<b>Revision</b>	0
<b>SDS number</b>	684
<b>Hazard statements in full</b>	<p>H220 Extremely flammable gas.</p> <p>H222 Extremely flammable aerosol.</p> <p>H225 Highly flammable liquid and vapour.</p> <p>H226 Flammable liquid and vapour.</p> <p>H229 Pressurised container: may burst if heated</p> <p>H280 Contains gas under pressure; may explode if heated.</p> <p>H312 Harmful in contact with skin.</p> <p>H315 Causes skin irritation.</p> <p>H319 Causes serious eye irritation.</p> <p>H336 May cause drowsiness or dizziness.</p>

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.